



# 3 IN1 CURRENT TRANSFORMER

- Cost Effective Three-Phase Molded Case
- Ratio,s Ranging From 60/5 To 630/5
- Plug-in Quite Connection 80% Labor Saving
- Lockable Terminal for Safety
- Both Available for Busbar or Din Rail Mounted.



Ration (A)	BURDNRN (VA)	
	CLASS 0.5	CLASS 1.0
60/1	-	1
100/1	-	1.5
125/1	1.5	1.5
150/1	1.5	1.5
300/1	1.5	1.5
100/1	-	1.5
125/1	-	1.5
150/1	-	1.5
160/1	1.5	1.5
200/1	1.5	1.5
250/1	1.5	1.5
250/1	1.5	1.5
300/1	2.5	2.5
400/1	2.5	2.5
500/1	2.5	2.5

SPECIFICATION	
System Voltage	720V maximum
Test Voltage	3kV for 1 minute
System Frequency	50Hz or 60Hz
Primary Ratings	60A to 630A
Short Circuit Thermal	60 x rated primary current
Overload withstand	1.2 x rated current continuously
Rated Dynamic Current	2.55 x Ith
Secondary Terminals	M4 screw terminals
Enclosure	Flame retardant grad classified UL 94V-0
Aperture Holes Centers	25,35,45mm
Mounting Hand ware	Plug-in metal feet for wall or base Mounting
	Bus-bar and DIN-rail
Compliant	IEC/EN60044-1

## DIMENSIONS

