



3 IN1 CURRENT TRANSFORMER

- Cost Effective Three-Phase Molded Case
- Ratio,s Ranging From 60/5 To 630/5
- Integrated wire sealable terminal cover
- Busbas, DIN-rail metal feet mounting
- Combined M4 posi/slot screwhardware supplied



Ration (A)	BURDNRN (VA)	
	CLASS 0.5	CLASS 1.0
60/5	-	1
100/5	1.5	1.5
125/5	1.5	1.5
150/5	1.5	1.5
200/5		1.5
	-	
100/5	-	1.5
125/5	-	2.5
150/5	1.5	3.75
160/5	1.5	1.5
200/5	1.5	1.5
250/5		1.5
	1.5	
250/5	2.5	1.5
300/5	2.5	2.5
400/5	2.5	2.5
500/5	2.5	2.5
600/5	2.5	2.5
630/5		2.5

SPECIFICATION	
Rated Current	60A to 630A loads
Rated Output	5A (AC)
Accuracy	Class 0.5 or 1 from 20% to 120% of rated current
Phase Angle	Less than 2 degrees at 50% of rated current
Insulation Voltage	600 Vac
Maximum Primary	5000 Vac (Insulated Conductor)
Dielectric Strength	2.°C
Operating Temperature	
Operating Humidity	
Case Material	
Bobbin	
Internal Structure	

DIMENSIONS

