



# MINI SPLIT CORE CURRENT TRANSFORMER

- Split Core, Easy Installtion
- Primary Input 5A ~ 6000A
- Secondary Output 333mV
- Safe Mode



RATED AMPS	OUTPUT	ACCURACY
5	0.333	0.5 or 1
10	0.333	0.5 or 1
20	0.333	0.5 or 1
50	0.333	0.5 or 1
75	0.333	0.5 or 1
5	0.1	0.5 or 1
10	0.1	0.5 or 1
20	0.1	0.5 or 1
50	0.1	0.5 or 1
75	0.1	0.5 or 1
5	0.333	0.5 or 1
10	0.333	0.5 or 1
50	0.333	0.5 or 1
100	0.333	0.5 or 1
150	0.333	0.5 or 1
5	0.1	0.5 or 1
10	0.1	0.5 or 1
50	0.1	0.5 or 1
100	0.1	0.5 or 1
150	0.1	0.5 or 1
10	0.333	0.5 or 1
50	0.333	0.5 or 1
100	0.333	0.5 or 1
250	0.333	0.5 or 1
300	0.333	0.5 or 1
10	0.1	0.5 or 1
50	0.1	0.5 or 1
100	0.1	0.5 or 1
250	0.1	0.5 or 1
300	0.1	0.5 or 1

SPECIFICATION	
Frequency	50-60Hz
Rated Current	5A to 600A loads
Rated Output	333mV/100mV (AC)
Accuracy	Class 0.5 or 1 from 20% to 120% of rated current
Phase Angle	less than 2 degrees at 50% of rated current
Insulation Voltage	600Vac
Maximum Primary	5000Vac (Insulated Conductor)
Dielectric Strength	2.5KV/1mA/1min
Operating Temperature	-15°Cto 60°C.
Operating Humidity	<85%
Case	PC / UL94-V0
Material	PBT
Bobbin	Permalloy
Core	Epoxy
Internal Structure	UL 1015, Twisted Pair, 22AWG

## DIMENSIONS

