





MULTI-FUNCTION TIME RELAY

Model No: SMART-MTR 151

- Microcontroller Based
- 10 Operating Modes
- Modular Design 18mm Wide Housing
- 10 Time Range (1s, 10s, 1m, 10m, 10h, 1d, 10d, On, Off)
- 1 Change Over Contact
- LED Indication for Power Supply and Relay Status.
- Din-Rail Mounting.




DIMENSIONS



SPECIFICATION		
Supply Terminals	A1,A2	A1,A2,A3
Pulse Terminal	S	
Supply Voltage	AC 220V	A1-A2: AC 220V A3-A2: AC/DC 24V
Rated Frequency	50/60Hz	
Time Range	0.1s-10days	
Repetition Accuracy	<5%	
Data Readout	<0.2%	
Data Storage	1 C/O	
Output Contacts	8A /AC1	
Current Rating	AC-15: 2A	
Contacts Capaciting	250V	
Insulation Voltage	IP20	
Protection Degree	3	
Pollution Degree	10 ⁵	
Electrical Life	10 ⁶	
Altitude	≤2000m	
Ambient Temperature	-5°C~+40°C	
Storage Temperature	-10°C~+50°C	
Wire Size	0.5mm ² ~ 1mm ²	
Torque	0.5Nm	
Mounting	TH-35 DIN-Rail	

 **DIMENSIONS**



 **WIRING DIAGRAM**

