



SOLID CORE CURRENT TRANSFORMER

- Two Built in Fixing Methods
- Built in Hinged Terminal Cover
- Built in Transparent Cover
- Wide Range Accuracy (3,1,0.5,0.2,0.2s)



INTRODUCTION

Perfect designed plastic case current transformer advanced snap on body high accuracy (up to Class 0.2s), humanization transparent cover and lead seal hole design makes the CT very easy to identify after long term use and perfect anti s tealing electricity.

SPECIFICATION	
Rated Frequency	50Hz-60Hz
Rated Current	5A to 5000A loads
Rated Output	5A, 1A, 0.5A, 0.25A, 0.1A
Accuracy	± 1% from 20% to 120% of rated current
Rated Short-Time	60In
Rated Voltage (Um)	1.2In
Operating Temperature	-10°C~50°C
Housing Self-Extinguishing Class	V0
Standard	IEC60044-1, EN60044-1, VDE0414-44-1, GB1208

RATIO (A)	BURDEN (VA)	
	CLASS 0.5	CLASS
50/5	1.5	2.5
60/5	1.5	2.5
75/5	2.5	3.75
100/5	3.75	5
150/5	5	5
200/5	5	5
250/5	5	5
300/5	5	5
75/5	1.5	1.5
80/5	1.5	1.5
100/5	2.5	2.5
150/5	3.75	5
200/5	5	5
250/5	5	5
300/5	5	5
400/5	5	5
500/5	5	5

