



# SPLIT CORE CURRENT TRANSFORMER

- Split Core, Easy Installtion
- Primary Input 5A~3000A
- Secondary Output 333mV
- Wide Inner Window Allowing
- Clamping of Big Cable



RATED AMPS	OUTPUT	ACCURACY
5	0.333V	1
10	0.333V	1
50	0.333V	1
75	0.333V	1
100	0.333V	1
125	0.333V	1
150	0.333V	1
200	0.333V	1
50	0.333V	1
100	0.333V	1
200	0.333V	1
250	0.333V	1
400	0.333V	1
600	0.333V	1
630	0.333V	1
100	0.333V	1
125	0.333V	1
250	0.333V	1
400	0.333V	1
630	0.333V	1
800	0.333V	1
1000	0.333V	1
2000	0.333V	1
400	0.333V	1
800	0.333V	1
1000	0.333V	1
1500	0.333V	1
2500	0.333V	1
3000	0.333V	1

SPECIFICATION	
Frequency	50-60Hz
Rated Current	5A to 3000A loads
Rated Output	333mV (AC)
Accuracy	± 1% from 20% to 120% of rated current
Phase Angle	less than 2 degrees at 50% of rated current
Insulation Voltage	600Vac
Maximum Primary	5000Vac (Insulated Conductor)
Dielectric Strength	2.5KV/1mA/1min
Operating Temperature	-15°C to 60°C.
Operating Humidity	<85%
Case Material	PC / UL94-V0
Bobbin	PBT
Core	Permalloy
Internal Structure	Epoxy
Leads	UL 1015, Twisted Pair, 22AWG

## DIMENSIONS

